

# SAFETY DATA SHEET Swarfega Stop Quick Aerosol

According to Regulation (EC) No 1907/2006, Annex II, as amended.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name Swarfega Stop Quick Aerosol

Product number SSQ500ML

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Car maintenance product.

## 1.3. Details of the supplier of the safety data sheet

Supplier

Deb Ltd

Denby Hall Way

Denby Derbyshire DE5 8JZ

Main Tel. 01773 855100 Technical Tel 01773 855105

reach@deb.co.uk

### 1.4. Emergency telephone number

Emergency telephone National Poisons Information Service (UK) 0344 8920111 (Health Professionals only)

## **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Skin Irrit. 2 - H315 STOT SE 3 - H336

Environmental hazards Aquatic Chronic 2 - H411

## 2.2. Label elements

### **Pictogram**







Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Revision date: 21/06/2017 Revision: 3 Supersedes date: 18/05/2015

## Swarfega Stop Quick Aerosol

**Precautionary statements** P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing vapour/ spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P501 Dispose of contents/ container in accordance with national regulations.

Contains NAPTHA (PETROLEUM), HYDROTREATED LIGHT, PROPAN-2-OL

Supplementary precautionary

P211 Do not spray on an open flame or other ignition source.

statements

P251 Do not pierce or burn, even after use.

P264 Wash contaminated skin thoroughly after handling. P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P332+P313 If skin irritation occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P312 Call a POISON CENTER/ doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

### SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

## NAPTHA (PETROLEUM), HYDROTREATED LIGHT

60-100%

CAS number: 64742-49-0 EC number: 921-024-6 REACH registration number: 01-

2119475514-35-XXXX

### Classification

Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

PROPAN-2-OL 10-30%

CAS number: 67-63-0 EC number: 200-661-7 REACH registration number: 01-

2119457558-25-XXXX

## Classification

Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336

BUTANE 5-10%

CAS number: 106-97-8 EC number: 203-448-7

#### Classification

Flam. Gas 1 - H220

The full text for all hazard statements is displayed in Section 16.

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

**General information** Move affected person to fresh air at once. Get medical attention if any discomfort continues.

**Inhalation** Move affected person to fresh air at once. When breathing is difficult, properly trained

personnel may assist affected person by administering oxygen. Keep affected person warm

and at rest. Get medical attention immediately.

**Ingestion** Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Give

milk instead of water if readily available. Never give anything by mouth to an unconscious

person. Get medical attention if any discomfort continues.

Skin contact Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Get medical attention if any discomfort continues.

### 4.2. Most important symptoms and effects, both acute and delayed

**Inhalation** Vapours may cause headache, fatigue, dizziness and nausea.

**Ingestion** Fumes from the stomach contents may be inhaled resulting in the same symptoms as

inhalation.

**Skin contact** Prolonged skin contact may cause redness and irritation.

**Eye contact** Irritation of eyes and mucous membranes.

## 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

## SECTION 5: Firefighting measures

## 5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray,

fog or mist.

### 5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion

products

Oxides of carbon.

## 5.3. Advice for firefighters

Protective actions during firefighting

Containers close to fire should be removed or cooled with water. Use water to keep fire

exposed containers cool and disperse vapours.

### SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

#### 6.2. Environmental precautions

Environmental precautions Avoid discharge to the aquatic environment. Collect and dispose of spillage as indicated in

Section 13.

## 6.3. Methods and material for containment and cleaning up

Revision date: 21/06/2017 Revision: 3 Supersedes date: 18/05/2015

## Swarfega Stop Quick Aerosol

### Methods for cleaning up

Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion. If leakage cannot be stopped, evacuate area.

#### 6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13. See Section 11

for additional information on health hazards.

### SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Avoid spilling. Wear suitable protective

equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. Avoid

inhalation of vapours. Avoid contact with skin, eyes and clothing.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

### SECTION 8: Exposure Controls/personal protection

#### 8.1. Control parameters

### Occupational exposure limits

## PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³ Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

### **BUTANE**

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

## PROPAN-2-OL (CAS: 67-63-0)

**DNEL** Workers - Inhalation; Long term systemic effects: 500 mg/m³

Workers - Dermal; Short term systemic effects: 888 mg/kg/day

General population - Inhalation; Long term systemic effects: 89 mg/m³ General population - Dermal; Long term systemic effects: 319 mg/kg/day General population - Oral; Long term systemic effects: 26 mg/kg/day

PNEC - Fresh water; 140.9 mg/l

- Marine water; 140.9 mg/l - Intermittent release: 140.9 mg/l

- STP; 2251 mg/l

Sediment (Freshwater); 552 mg/kgSediment (Marinewater); 552 mg/kg

- Soil; 28 mg/kg

#### 8.2. Exposure controls

### Protective equipment





Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible.

**Hand protection** Use protective gloves. It is recommended that gloves are made of the following material:

Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are

recommended.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapour contact.

Hygiene measures DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating,

smoking and using the toilet. Promptly remove any clothing that becomes contaminated.

When using do not eat, drink or smoke.

**Respiratory protection**No specific recommendations. Respiratory protection must be used if the airborne

contamination exceeds the recommended occupational exposure limit.

### **SECTION 9: Physical and Chemical Properties**

### 9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour Typical

Odour Characteristic.

Flash point -15°C

Upper/lower flammability or

explosive limits

Lower flammable/explosive limit: 0.8% Upper flammable/explosive limit: 9.0%

Solubility(ies) Insoluble in water

9.2. Other information

Other information None.

### **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

**Reactivity** Vapours may form explosive mixtures with air.

10.2. Chemical stability

**Stability** Stable at normal ambient temperatures.

## 10.3. Possibility of hazardous reactions

Possibility of hazardous

Not determined.

reactions

## 10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:

Strong oxidising agents. Strong alkalis. Strong mineral acids.

### 10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

#### 10.6. Hazardous decomposition products

Hazardous decomposition

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

products

## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Inhalation May cause respiratory system irritation. Vapours may cause headache, fatigue, dizziness and

nausea. Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal

symptoms, including upset stomach.

Skin contact Product has a defatting effect on skin. May cause skin irritation/eczema. Prolonged or

repeated exposure may cause severe irritation.

**Eye contact** Irritating to eyes. May cause chemical eye burns.

Route of entry Inhalation Skin and/or eye contact.

### SECTION 12: Ecological Information

**Ecotoxicity** Dangerous for the environment if discharged into watercourses.

## 12.1. Toxicity

## 12.2. Persistence and degradability

Persistence and degradability The product is expected to be slowly biodegradable. The surfactant(s) contained in this

product complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them at their direct

request, or at the request of a detergent manufacturer.

## 12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

**Mobility** The product has poor water-solubility.

## 12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

#### 12.6. Other adverse effects

Other adverse effects None known.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

General information Do not puncture or incinerate even when empty. Waste is classified as hazardous waste.

Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

**Disposal methods** Empty containers must not be punctured or incinerated because of the risk of an explosion.

Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

### **SECTION 14: Transport information**

### 14.1. UN number

UN No. (ADR/RID) 1950 UN No. (IMDG) 1950 UN No. (ICAO) 1950

### 14.2. UN proper shipping name

Proper shipping name

AEROSOLS (NAPTHA (PETROLEUM), HYDROTREATED LIGHT)

(ADR/RID)

Proper shipping name (IMDG) AEROSOLS (NAPTHA (PETROLEUM), HYDROTREATED LIGHT)

Proper shipping name (ICAO) AEROSOLS (NAPTHA (PETROLEUM), HYDROTREATED LIGHT)

Proper shipping name (ADN) AEROSOLS (NAPTHA (PETROLEUM), HYDROTREATED LIGHT)

## 14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

## Transport labels



### 14.4. Packing group

Not applicable.

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



## 14.6. Special precautions for user

**EmS** F-D, S-U

Tunnel restriction code (D)

## 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not relevant.

Annex II of MARPOL 73/78

and the IBC Code

### SECTION 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** legislation Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative

occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at

work (as amended).

Commission Directive 91/322/EEC of 29 May 1991 on establishing indicative limit values by implementing Council Directive 80/1107/EEC on the protection of workers from the risks

related to exposure to chemical, physical and biological agents at work.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Guidance Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### **SECTION 16: Other information**

Revision comments Commission Regulation (EU) No 2015/830 of 28 May 2015. NOTE: Lines within the margin

indicate significant changes from the previous revision.

Revision date 21/06/2017

Revision 3

Supersedes date 18/05/2015

Hazard statements in full H220 Extremely flammable gas.

> H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H229 Pressurised container: may burst if heated

> H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

**Notes for Hazard Statements** 

in Full

The full text for Hazard Statements in section 16 relates to the reference numbers in sections

2 and 3 and not necessarily the finished product classification.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.