

**Material Safety Data Sheet**

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

**U. S. Department of Labor**

Occupational Safety and Health Administration  
(Non-Mandatory Form)  
Form Approved  
OMB No. 1218-0072

<b>IDENTIFY (As used on label)</b> Perma-Lock # 27106, 27113, 27136		NOTE: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate it.	
<b>Section I</b>			
Manufacture's Name: J-B WELD COMPANY, LLC		For UK Branch: J-B Weld, Automotive Brands Building Bidavon Industrial Estate, Bidford-Upon-Avon, Warwickshire, B50 4JN, Phone: 0871 288 7125	
Address (Number, Street, City, State and ZIP Code)		Telephone Number for Information: 1-800-529-3530	
1130 COMO STREET		Data Prepared: 02/09/11	
SULPHUR SPRINGS, TX 75482		Signature of Preparer (Optional)	
<b>Section II – Hazardous Ingredients/Identity Information</b>			
Hazardous Components (Specify Chemical Identity: Common Name(s) OSHA PEL ACGIH TLV Other Limits Recommended % Optional)			
Polyglycol Dimethacrylate	25852-47-5		60–90
Polyester Resin	Trade Secret		10–30
Cumene Hydroperoxide*	80-15-9		1–5
Saccharin*	81-07-2		1–5
Methanol*	67-56-1		0.1–1.0
NN Di-Alkyltoluidine	613-48-9		0.1–1.0
Optical brightner	Trade Secret		0.05 – 0.15
Cumene	98-82-8		0.05 – 0.15
*This component is listed as SARA Section 313 Toxic Chemicals.			
<b>Section III – Physical/Chemical Characteristics</b>			
Boiling Point	> 400°F @ 760mm	Specific Gravity (H2O=1) 20 C	1.1 – 1.13
Vapor Pressure (mm Hg)	<5	Melting Point	N/A
Vapor Density (AIR = 1)	1.01	Evaporation Rate (Butyl Acetate = 1)	Low
Solubility in Water Slight			
Appearance and Odor: Thin red liquid, mild organic odor			
<b>Section IV – Fire and Explosion Hazard Data</b>			
Flash Point (Method Used)	>212°F TOC	Flammable Limits	LEL N/A UEL N/A
Extinguishing Media: Use fire extinguisher with class B extinguishing agents (e.g., dry chemical, carbon dioxide)			
Special Fire Fighting Procedures: Self contained breathing apparatus. Water may not effectively extinguish fire. It may be used to keep containers and surfaces cool and prevent explosive rupture.			
Unusual Fire and Explosion Hazards: Irritating Organic Vapors			
<b>Section V – Health Hazard Data</b>			
Threshold Limit Value: Cumene: ACGIH:TWA 50 ppm; OSHA: TWA 50 ppm, Cumene hydroperoxide AIHA: 1 ppm (cutaneous) Methanol: ACGIH:TWA 200 ppm, STEL 250 ppm ; OSHA: TWA 200 ppm, STEL 250 ppm (cutaneous) Effects of overexposure: <b>Skin:</b> Moderate skin irritation. Prolonged skin contact may result in dermatitis in sensitive persons. <b>Eyes:</b> Severe eye irritant. Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea and impaired vision. Vapors released during cure may cause eye irritation. <b>Inhalation:</b> Respiratory tract irritation: signs/symptoms may include coughing, sneezing, nasal discharge, headache, hoarseness and nose and throat pain. <b>Ingestion:</b> Gastrointestinal irritation. May include abdominal pain, stomach upset, nausea, vomiting and diarrhea.			

**Target Organ effects:** Prolonged or repeated exposure may cause neurological effects such as personality changes, lack of coordination, sensory loss, tremors, and/or changes in blood pressure and heart rate. Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Emergency and First Aid Procedures:

**Skin:** Remove contaminated clothing and shoes. Wash with abrasive soap and water. Acetone or alcohol may be helpful. Wash contaminated clothing and clean shoes before reuse.

**Eyes:** Immediately flush with plenty of water for 15 minutes. Seek medical attention.

**Inhalation:** Remove person to fresh air. If signs/symptoms develop seek medical attention.

**Ingestion:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Get immediate medical attention for ingesting methacrylates.

**Section VI – Reactivity Data**

Stability	Unstable		Conditions to Avoid: Reducing agents
	Stable	X R	

**Incompatibility (Materials to avoid):**

Heat; Light; Strong oxidizing materials

Hazardous Decomposition Products:

During combustion: formaldehyde, oxides of carbon, nitrogen and sulfur

Hazardous Polymerization	May occur	X	Conditions to Avoid: Temperatures in excess of 150°F
	Will not occur		

**Section VII – Spill or Leak Procedures**

Steps to be taken in case material is to be released or spilled:

Soak up with inert absorbent. Dispose into closed container.

Waste Disposal Method:

Landfill or incinerate in accordance with EPA and Local regulations.

EPA Hazardous waste number (RCRA): Not regulated.

**Section VIII – Special Protective Information**

**Respiratory Protection (Specify Type)**

None needed for normal use.

Ventilation	Local Exhaust Recommended	Special None
	Mechanical Not Applicable	Other None

**Protective Gloves:**

Butyl rubber, Viton, Neoprene or PVA gloves

**Eye Protection:**

Safety Glasses with side shields

**Other Protective Equipment:**

Eye wash stations and safety showers.

**Section IX – Special Precautions**

Precautions to be taken in handling and storing:

Store in a cool dry place and out of direct sunlight.

Other Precautions:

Keep away from children. Avoid contact with skin, eyes and clothing.

**Section X – Regulatory Information**

Sara (311,312) Hazard class: Acute Health Hazard, Chronic Health Hazard

Section 313 Toxic chemical reporting requirements: Cumene hydroperoxide 1-5 wt%. (10 pounds)

TSCA 8 (b) Inventory status: All components are listed or exempt from listing on the TSCA Inventory.

Estimated HMIS Code: Health Hazard (2) Fire Hazard (1) Reactivity (1)

WHMIS Hazard Class: D2B

**Section X – Transportation Information**

DOT (49 CFR 172)

Proper Shipping Name: Unrestricted

UN#: None

Packaging Group: None

Hazard Classification: Unrestricted

Information presented herein has been compiled from sources considered to be accurate and reliable, but is not guaranteed to be so. Nothing herein shall be considered as recommending practices or products in violation of any patent, law or regulation. It is the user's responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. WE MAKE NO WARRANTIES REGARDING THE PRODUCTS AND DISCLAIM ALL EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.