



## SAFETY DATA SHEET BLACK TRIM WAX

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name                      BLACK TRIM WAX  
Product No.                        ATW375, BTW375, HBC000, NBW375, RBW375, PBT375, MBT500

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses                    Car maintenance product.

#### 1.3. Details of the supplier of the safety data sheet

Supplier                            TETROSYL LIMITED  
    Bury  
    Lancashire  
    England  
    BL9 7NY  
    0161 764 5981  
    0161 797 5899  
    info@tetrosyl.com  
Manufacturer                      TETROSYL LIMITED  
    Bury  
    Lancashire  
    England  
    BL9 7NY  
    0161 764 5981  
    0161 797 5899  
    info@tetrosyl.com

#### 1.4. Emergency telephone number

0161 764 5981

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards	Flam. Liq. 3 - H226
Human health	Not classified.
Environment	Not classified.

Classification (1999/45/EEC) R10.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.  
Environment

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

#### 2.2. Label elements

**BLACK TRIM WAX**

Label In Accordance With (EC) No. 1272/2008



Signal Word	Warning	
Hazard Statements		
Precautionary Statements	H226	Flammable liquid and vapour.
	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
	P501	Dispose of contents/container in accordance with local regulations.
Supplementary Precautionary Statements		
	P233	Keep container tightly closed.
	P240	Ground/bond container and receiving equipment.
	P241	Use explosion-proof electrical equipment.
	P242	Use only non-sparking tools.
	P243	Take precautionary measures against static discharge.
	P280	Wear protective gloves/protective clothing/eye protection/face protection.
	P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P370+378	In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction.
	P403+235	Store in a well-ventilated place. Keep cool.

**2.3. Other hazards**

This product does not contain any PBT or vPvB substances.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixtures**

HYDROCARBONS, C9 - C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS		5.0 - <10.0%
CAS-No.:	EC No.: 919-857-5	Registration Number: 01-2119463258-33-XXXX
Classification (EC 1272/2008)	Classification (67/548/EEC)	
Flam. Liq. 3 - H226	Xn;R65.	
EUH066	R10,R66,R67.	
STOT SE 3 - H336		
Asp. Tox. 1 - H304		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**SECTION 4: FIRST AID MEASURES**

## BLACK TRIM WAX

### **4.1. Description of first aid measures**

#### General information

Remove affected person from source of contamination. NOTE! Effects may be delayed. Keep affected person under observation. Get medical attention. CAUTION! First aid personnel must be aware of own risk during rescue! Move the exposed person to fresh air at once. NOTE! Keep affected person away from heat, sparks and flames! Perform artificial respiration if breathing has stopped. Place unconscious person on the side in the recovery position and ensure breathing can take place.

#### Inhalation

Remove victim immediately from source of exposure. Move injured person into fresh air and keep person calm under observation. If uncomfortable: Seek hospital and bring these instructions. Place unconscious person on the side in the recovery position and ensure breathing can take place. Perform artificial respiration if breathing has stopped.

#### Ingestion

Get medical attention immediately! Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and bring along these instructions. Do not give victim anything to drink if he is unconscious. NOTE! Keep affected person away from heat, sparks and flames! When risk of unconsciousness, place and transport the victim in secured side position.

#### Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Consult a physician for specific advice.

#### Eye contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Do not rub eye. Get medical attention if any discomfort continues.

### **4.2. Most important symptoms and effects, both acute and delayed**

#### General information

The severity of the symptoms described will vary dependant of the concentration and the length of exposure. NOTE! Effects may be delayed. Keep affected person under observation.

#### Inhalation

In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death. Vapours may cause headache, fatigue, dizziness and nausea. In high concentrations, vapours are anaesthetic and may cause headache, fatigue, dizziness and central nervous system effects.

#### Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication. May cause chemical burns in mouth and throat. Central nervous system depression. Fumes from the stomach contents may be inhaled resulting in the same symptoms as inhalation.

#### Skin contact

Prolonged contact may cause redness, irritation and dry skin.

#### Eye contact

Irritation, burning, lachrymation, blurred vision after liquid splash.

### **4.3. Indication of any immediate medical attention and special treatment needed**

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

## SECTION 5: FIREFIGHTING MEASURES

### **5.1. Extinguishing media**

#### Extinguishing media

Use: Foam, carbon dioxide or dry powder. Water. Use fire-extinguishing media appropriate for surrounding materials.

## BLACK TRIM WAX

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

### **5.2. Special hazards arising from the substance or mixture**

Hazardous combustion products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

Unusual Fire & Explosion Hazards

HIGHLY FLAMMABLE! Forms explosive mixtures with air. Vapours are heavier than air and may spread near ground to sources of ignition. May travel considerable distance to source of ignition and flash back.

Specific hazards

Vapours may form explosive air mixtures even at room temperature. Vapours are heavier than air and may travel along the floor and in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember.

### **5.3. Advice for firefighters**

Special Fire Fighting Procedures

Avoid breathing fire vapours. Keep up-wind to avoid fumes. Be aware of risk of fire re-starting, and risk of explosion. Cool containers exposed to flames with water until well after the fire is out. Use water SPRAY only to cool containers! Do not put water on leaked material.

Protective equipment for fire-fighters

Leave danger zone immediately.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### **6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective clothing as described in Section 8 of this safety data sheet. In case of inadequate ventilation, use respiratory protection. Take precautionary measures against static discharges. Do not smoke, use open fire or other sources of ignition. Do not breathe vapour. Avoid contact with skin and eyes. In case of spills, beware of slippery floors and surfaces.

### **6.2. Environmental precautions**

Do not discharge into drains, water courses or onto the ground. Prevent entry into drains. Avoid discharge to the aquatic environment.

### **6.3. Methods and material for containment and cleaning up**

For waste disposal, see section 13. Stop leak if possible without risk. Collect with absorbent, non-combustible material into suitable containers. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Provide ventilation and confine spill. Do not allow runoff to sewer. Cover large spillages with alcohol-resistant foam.

### **6.4. Reference to other sections**

Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

## SECTION 7: HANDLING AND STORAGE

### **7.1. Precautions for safe handling**

Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Keep away from heat, sparks and open flame. Risk of vapour concentration on the floor and in low-lying areas. Static electricity and formation of sparks must be prevented. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. Observe good chemical hygiene practices. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Mechanical ventilation or local exhaust ventilation may be required.

### **7.2. Conditions for safe storage, including any incompatibilities**

Keep away from heat, sparks and open flame. Keep containers tightly closed. Keep upright. Keep in original container. Avoid contact with oxidising agents. Do not store near heat sources or expose to high temperatures. Store separated from: Oxidising material.

**BLACK TRIM WAX**

Storage Class

Flammable liquid storage.

**7.3. Specific end use(s)**

The identified uses for this product are detailed in Section 1.2.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters****8.2. Exposure controls**

Protective equipment



Process conditions

Provide eyewash station.

Engineering measures

Provide explosion proof ventilation for high concentrations. Observe occupational exposure limits and minimize the risk of inhalation of vapours. All handling to take place in well-ventilated area.

Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided. Check that mask fits tight and change filter regularly. Use respiratory equipment with gas filter, type AX.

Hand protection

For prolonged or repeated skin contact use suitable protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.

Eye protection

Wear approved, tight fitting safety glasses where splashing is probable.

Other Protection

Wear suitable protective clothing as protection against splashing or contamination.

Hygiene measures

Wash promptly with soap &amp; water if skin becomes contaminated. When using do not eat, drink or smoke.

Isolate contaminated clothing and wash before reuse.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties**

Appearance	Viscous liquid.
Colour	Black.
Odour	Perfume.
Solubility	Slightly soluble in water.
Initial boiling point and boiling range (°C)	100°C
Melting point (°C)	Scientifically unjustified.
Relative density	0.955 - 0.975 20

**BLACK TRIM WAX**

Vapour density (air=1)  
Scientifically unjustified.  
Vapour pressure  
Scientifically unjustified.  
Evaporation rate  
Scientifically unjustified.  
pH-Value, Conc. Solution 7.0 - 9.0  
Viscosity 800 - 2000 cP 20°C  
Decomposition temperature (°C)  
Scientifically unjustified.  
Odour Threshold, Lower  
Scientifically unjustified.  
Odour Threshold, Upper  
Scientifically unjustified.  
Flash point (°C) 40°C  
Auto Ignition Temperature (°C)  
Scientifically unjustified.  
Flammability Limit - Lower(%)  
Scientifically unjustified.  
Flammability Limit - Upper(%)  
Scientifically unjustified.  
Partition Coefficient  
(N-Octanol/Water)  
Scientifically unjustified.  
Oxidising properties  
Not determined.

**9.2. Other information**

None.

**SECTION 10: STABILITY AND REACTIVITY****10.1. Reactivity**

No specific reactivity hazards associated with this product.

**10.2. Chemical stability**

Stable under normal temperature conditions and recommended use.

**10.3. Possibility of hazardous reactions**

Not relevant

**10.4. Conditions to avoid**

Avoid heat, flames and other sources of ignition.

**10.5. Incompatible materials**

Materials To Avoid

No specific, or groups of materials are likely to react to produce a hazardous situation.

**10.6. Hazardous decomposition products**

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

**SECTION 11: TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects**

**BLACK TRIM WAX**

Toxic Dose 1 - LD 50  
>2000 mg/kg (oral rat)

**General information**

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Contains small amounts of organic solvents. Extensive use of the product in areas with inadequate ventilation may result in hazardous vapour concentrations.

**Inhalation**

Vapour may irritate respiratory system or lungs.

**Ingestion**

Pneumonia may be the result if vomited material containing solvents reaches the lungs.

**Skin contact**

Repeated exposure may cause skin dryness or cracking.

**Eye contact**

Irritating and may cause redness and pain. Spray and vapour in the eyes may cause irritation and smarting.

**Health Warnings**

This chemical can be hazardous when inhaled and/or touched. May cause severe internal injury. Vapour from this chemical can be hazardous when inhaled.

**Route of entry**

Inhalation. Ingestion. Skin and/or eye contact. Skin absorption.

**Target Organs**

Skin Central nervous system Eyes Respiratory system, lungs

**Medical Symptoms**

Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo.

**Medical Considerations**

Skin disorders and allergies.

**SECTION 12: ECOLOGICAL INFORMATION****Ecotoxicity**

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

**12.1. Toxicity**

LC 50, 96 Hrs, Fish mg/l 1-10

**12.2. Persistence and degradability****Degradability**

No data available.

**12.3. Bioaccumulative potential****Bioaccumulative potential**

No data available on bioaccumulation.

**Partition coefficient**

Scientifically unjustified.

**12.4. Mobility in soil**

**BLACK TRIM WAX****Mobility:**

The product is partly miscible with water and may spread in the aquatic environment.

**Adsorption/Desorption Coefficient**

Not available.

**12.5. Results of PBT and vPvB assessment**

Not Classified as PBT/vPvB by current EU criteria.

**12.6. Other adverse effects**

Not available.

**SECTION 13: DISPOSAL CONSIDERATIONS****General information**

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority. Do not puncture or incinerate even when empty.

**13.1. Waste treatment methods**

Confirm disposal procedures with environmental engineer and local regulations. Make sure containers are empty before discarding (explosion risk). Empty containers must not be burned because of explosion hazard. Recover and reclaim or recycle, if practical.

**SECTION 14: TRANSPORT INFORMATION****14.1. UN number**

UN No. (ADR/RID/ADN)	1993
UN No. (IMDG)	1993
UN No. (ICAO)	1993

**14.2. UN proper shipping name**

Proper Shipping Name      FLAMMABLE LIQUID, N.O.S. (PETROLEUM DISTILLATES, PIN-2-ENE)

**14.3. Transport hazard class(es)**

ADR/RID/ADN Class	3
ADR/RID/ADN Class	Class 3: Flammable liquids.
ADR Label No.	3
IMDG Class	3
ICAO Class/Division	3
Transport Labels	

**14.4. Packing group**

ADR/RID/ADN Packing group	III
IMDG Packing group	III
ICAO Packing group	III

**14.5. Environmental hazards**



**BLACK TRIM WAX**

Environmentally Hazardous Substance/Marine Pollutant  
No.

**14.6. Special precautions for user**

EMS	F-E, S-E
Emergency Action Code	3Y
Hazard No. (ADR)	30

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

**SECTION 15: REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

**15.2. Chemical Safety Assessment**

No chemical safety assessment has been carried out.

**SECTION 16: OTHER INFORMATION**

Revision Comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision Date	20/05/2015
Revision	18
Supersedes date	05/03/2015 v17
Safety Data Sheet Status	Approved.

Risk Phrases In Full

R10	Flammable
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

Hazard Statements In Full

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.