



## SAFETY DATA SHEET COLOUR CURE 2K FIBROFILL

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name COLOUR CURE 2K FIBROFILL  
Product No. CCF010, CCF020

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Supplier TETROSYL LIMITED  
Bury  
Lancashire  
England  
BL9 7NY  
0161 764 5981  
0161 797 5899  
info@tetrosyl.com

Manufacturer TETROSYL LIMITED  
Bury  
Lancashire  
England  
BL9 7NY  
0161 764 5981  
0161 797 5899  
info@tetrosyl.com

#### 1.4. Emergency telephone number

0161 764 5981

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards	Flam. Liq. 3 - H226
Human health	Acute Tox. 4 - H332; Skin Irrit. 2 - H315; Eye Irrit. 2 - H319; Repr. 2 - H361d; STOT RE 1 - H372
Environment	Not classified.

Classification (1999/45/EEC) Xn; R20. Xi; R36/38. R10.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### 2.2. Label elements

Contains STYRENE

Label In Accordance With (EC) No. 1272/2008

## COLOUR CURE 2K FIBROFILL



## Signal Word

Danger

## Hazard Statements

H226 Flammable liquid and vapour.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H361d Suspected of damaging the unborn child.  
 H372 Causes damage to organs through prolonged or repeated exposure.

## Precautionary Statements

P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 P270 Do not eat, drink or smoke when using this product.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P281 Use personal protective equipment as required.  
 P260 Do not breathe vapour/spray.  
 P261 Avoid breathing vapour/spray.  
 P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308+313 IF exposed or concerned: Get medical advice/attention.  
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with local regulations.

## Supplementary Precautionary Statements

P201 Obtain special instructions before use.  
 P233 Keep container tightly closed.  
 P240 Ground/bond container and receiving equipment.  
 P241 Use explosion-proof electrical equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P264 Wash contaminated skin thoroughly after handling.  
 P321 Specific treatment (see medical advice on this label).  
 P370+378 In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction.  
 P302+352 IF ON SKIN: Wash with plenty of soap and water.  
 P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

**COLOUR CURE 2K FIBROFILL**

P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P313	Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P332+313	If skin irritation occurs: Get medical advice/attention.
P337	If eye irritation persists:
P362	Take off contaminated clothing and wash before reuse.
P403+235	Store in a well-ventilated place. Keep cool.

**2.3. Other hazards****SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixtures**

AMORPHOUS SILICON DIOXIDE, CHEMICALLY PREPARED	0.3 - <0.5%
CAS-No.: 7631-86-9	EC No.: 231-545-4
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.
BUTYL GLYCOL	0.1 - <0.3%
CAS-No.: 111-76-2	EC No.: 203-905-0
	Registration Number: 01-2119475108-36-XXXX
Classification (EC 1272/2008) Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319	Classification (67/548/EEC) Xn;R20/21/22 Xi;R36/38
STYRENE	10.0 - <20.0%
CAS-No.: 100-42-5	EC No.: 202-851-5
	Registration Number: 01-2119457861-32-0017
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361d STOT RE 1 - H372	Classification (67/548/EEC) R10 Xn;R20 Xi;R36/38

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**SECTION 4: FIRST AID MEASURES****4.1. Description of first aid measures**

## COLOUR CURE 2K FIBROFILL

### General information

Remove affected person from source of contamination. NOTE! Effects may be delayed. Keep affected person under observation. Get medical attention. CAUTION! First aid personnel must be aware of own risk during rescue! Move the exposed person to fresh air at once. NOTE! Keep affected person away from heat, sparks and flames! Perform artificial respiration if breathing has stopped. Place unconscious person on the side in the recovery position and ensure breathing can take place.

### Inhalation

Remove victim immediately from source of exposure. Move injured person into fresh air and keep person calm under observation. If uncomfortable: Seek hospital and bring these instructions. Place unconscious person on the side in the recovery position and ensure breathing can take place. Perform artificial respiration if breathing has stopped.

### Ingestion

Get medical attention immediately! Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and bring along these instructions. Do not give victim anything to drink if he is unconscious. NOTE! Keep affected person away from heat, sparks and flames! When risk of unconsciousness, place and transport the victim in secured side position.

### Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Rinse with water. Use suitable lotion to moisturise skin. Get medical attention promptly if symptoms occur after washing.

### Eye contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Do not rub eye. Get medical attention if any discomfort continues.

### **4.2. Most important symptoms and effects, both acute and delayed**

#### General information

The severity of the symptoms described will vary dependant of the concentration and the length of exposure. NOTE! Effects may be delayed. Keep affected person under observation.

#### Inhalation

In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death. Vapours may cause headache, fatigue, dizziness and nausea. In high concentrations, vapours are anaesthetic and may cause headache, fatigue, dizziness and central nervous system effects.

#### Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication. May cause chemical burns in mouth and throat. Central nervous system depression. Fumes from the stomach contents may be inhaled resulting in the same symptoms as inhalation.

#### Skin contact

Prolonged contact may cause redness, irritation and dry skin.

#### Eye contact

Irritation, burning, lachrymation, blurred vision after liquid splash.

### **4.3. Indication of any immediate medical attention and special treatment needed**

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

## **SECTION 5: FIREFIGHTING MEASURES**

### **5.1. Extinguishing media**

#### Extinguishing media

Use: Foam, carbon dioxide or dry powder. Water. Use fire-extinguishing media appropriate for surrounding materials.

#### Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

**COLOUR CURE 2K FIBROFILL****5.2. Special hazards arising from the substance or mixture**

Hazardous combustion products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

Unusual Fire & Explosion Hazards

HIGHLY FLAMMABLE! Forms explosive mixtures with air. Vapours are heavier than air and may spread near ground to sources of ignition. May travel considerable distance to source of ignition and flash back.

Specific hazards

Vapours may form explosive air mixtures even at room temperature. Vapours are heavier than air and may travel along the floor and in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember.

**5.3. Advice for firefighters**

Special Fire Fighting Procedures

Avoid breathing fire vapours. Keep up-wind to avoid fumes. Be aware of risk of fire re-starting, and risk of explosion. Cool containers exposed to flames with water until well after the fire is out. Use water SPRAY only to cool containers! Do not put water on leaked material.

Protective equipment for fire-fighters

Leave danger zone immediately.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective clothing as described in Section 8 of this safety data sheet. In case of inadequate ventilation, use respiratory protection. Take precautionary measures against static discharges. Do not smoke, use open fire or other sources of ignition. Do not breathe vapour. Avoid contact with skin and eyes. In case of spills, beware of slippery floors and surfaces.

**6.2. Environmental precautions**

Do not discharge into drains, water courses or onto the ground. Prevent entry into drains. Avoid discharge to the aquatic environment.

**6.3. Methods and material for containment and cleaning up**

For waste disposal, see section 13. Stop leak if possible without risk. Collect with absorbent, non-combustible material into suitable containers. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Provide ventilation and confine spill. Do not allow runoff to sewer. Cover large spillages with alcohol-resistant foam.

**6.4. Reference to other sections**

Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

**SECTION 7: HANDLING AND STORAGE****7.1. Precautions for safe handling**

Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Keep away from heat, sparks and open flame. Risk of vapour concentration on the floor and in low-lying areas. Static electricity and formation of sparks must be prevented. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. Observe good chemical hygiene practices. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Mechanical ventilation or local exhaust ventilation may be required.

**7.2. Conditions for safe storage, including any incompatibilities**

Keep away from heat, sparks and open flame. Keep containers tightly closed. Keep upright. Keep in original container. Avoid contact with oxidising agents. Do not store near heat sources or expose to high temperatures. Store separated from: Oxidising material.

Storage Class

Flammable liquid storage.

**COLOUR CURE 2K FIBROFILL****7.3. Specific end use(s)**

The identified uses for this product are detailed in Section 1.2.


**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters**

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
AMORPHOUS SILICON DIOXIDE, CHEMICALLY PREPARED	WEL		2.4 mg/m <sup>3</sup>			
BUTYL GLYCOL	WEL	25 ppm	123 mg/m <sup>3</sup>	50 ppm	246 mg/m <sup>3</sup>	Sk
STYRENE	WEL	100 ppm	430 mg/m <sup>3</sup>	250 ppm	1080 mg/m <sup>3</sup>	

WEL = Workplace Exposure Limit.  
Sk = Can be absorbed through skin.

**8.2. Exposure controls**

Protective equipment



Process conditions

Provide eyewash station.

Engineering measures

Provide explosion proof ventilation for high concentrations. Observe occupational exposure limits and minimize the risk of inhalation of vapours. All handling to take place in well-ventilated area.

Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided. Check that mask fits tight and change filter regularly. Use respiratory equipment with gas filter, type AX.

Hand protection

For prolonged or repeated skin contact use suitable protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.

Eye protection

Wear approved, tight fitting safety glasses where splashing is probable.

Other Protection

Wear suitable protective clothing as protection against splashing or contamination.

Hygiene measures

Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke.

Isolate contaminated clothing and wash before reuse.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties**

Appearance                      Fibrous Coloured paste.  
Colour                                Yellow.

**COLOUR CURE 2K FIBROFILL**

Odour of solvents  
Solubility Insoluble in water  
Initial boiling point and boiling range (°C) 145°C  
Melting point (°C)  
Not determined.  
Relative density 1.5 g/cm<sup>3</sup> 20  
Vapour density (air=1)  
Not determined.  
Vapour pressure  
Not determined.  
Evaporation rate  
Not determined.  
Viscosity >10, 000 cP 20  
Decomposition temperature (°C)  
Not determined.  
Odour Threshold, Lower  
Not determined.  
Odour Threshold, Upper  
Not determined.  
Flash point (°C) 31°C  
Auto Ignition Temperature (°C)  
Not determined.  
Flammability Limit - Lower(%)  
Not determined.  
Flammability Limit - Upper(%)  
Not determined.  
Partition Coefficient 2.96 @ 25°C  
(N-Octanol/Water)  
Oxidising properties  
Not available.

**9.2. Other information**

None.

**SECTION 10: STABILITY AND REACTIVITY****10.1. Reactivity**

The product may form explosive vapours/air mixtures even at normal room temperatures.

**10.2. Chemical stability**

Stable under normal temperature conditions and recommended use.

**10.3. Possibility of hazardous reactions**

Not relevant

**10.4. Conditions to avoid**

Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.

**10.5. Incompatible materials**

Materials To Avoid  
Strong oxidising substances.

**10.6. Hazardous decomposition products**

**COLOUR CURE 2K FIBROFILL**

None at ambient temperatures. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

**SECTION 11: TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects**

Toxic Dose 1 - LD 50  
5000 (Styrene) mg/kg (oral rat)

**General information**

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Contains small amounts of organic solvents. Extensive use of the product in areas with inadequate ventilation may result in hazardous vapour concentrations.

**Inhalation**

Vapours may irritate throat and respiratory system and cause headache, dizziness and dullness. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Contains organic solvents which in case of overexposure may depress the central nervous system causing dizziness and intoxication.

**Ingestion**

May cause internal injury. May cause nausea, headache, dizziness and intoxication. Harmful: may cause lung damage if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

**Skin contact**

Prolonged contact may cause dryness of the skin. Repeated exposure may cause skin dryness or cracking.

**Eye contact**

Irritating and may cause redness and pain. Spray and vapour in the eyes may cause irritation and smarting.

**Health Warnings**

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

**Route of entry**

Inhalation. Skin absorption. Ingestion. Skin and/or eye contact.

**Medical Symptoms**

Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo.

**Medical Considerations**

Risk of chemical pneumonia after aspiration.

**SECTION 12: ECOLOGICAL INFORMATION****Ecotoxicity**

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**12.1. Toxicity**

LC 50, 96 Hrs, Fish mg/l	25 (Styrene)
EC 50, 48 Hrs, Daphnia, mg/l	23 (Styrene)
IC 50, 72 Hrs, Algae, mg/l	4.7 (Styrene)

**12.2. Persistence and degradability****Degradability**

There are no data on the degradability of this product.



**COLOUR CURE 2K FIBROFILL****12.3. Bioaccumulative potential**

Bioaccumulative potential

No data available on bioaccumulation.

Partition coefficient 2.96 @ 25°C

**12.4. Mobility in soil**

Adsorption/Desorption Coefficient

Not available.

**12.5. Results of PBT and vPvB assessment**

Not Classified as PBT/vPvB by current EU criteria.

**12.6. Other adverse effects**

Not available.

**SECTION 13: DISPOSAL CONSIDERATIONS**

General information

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority. Do not puncture or incinerate even when empty.

**13.1. Waste treatment methods**

Confirm disposal procedures with environmental engineer and local regulations. Make sure containers are empty before discarding (explosion risk). Empty containers must not be burned because of explosion hazard. Recover and reclaim or recycle, if practical.

**SECTION 14: TRANSPORT INFORMATION****14.1. UN number**

UN No. (ADR/RID/ADN)	2055
UN No. (IMDG)	2055
UN No. (ICAO)	2055

**14.2. UN proper shipping name**

Proper Shipping Name STYRENE MONOMER, STABILIZED

**14.3. Transport hazard class(es)**

ADR/RID/ADN Class	3
ADR/RID/ADN Class	Class 3: Flammable liquids.
ADR Label No.	3
IMDG Class	3
ICAO Class/Division	3
Transport Labels	

**14.4. Packing group**

ADR/RID/ADN Packing group III

**COLOUR CURE 2K FIBROFILL**

IMDG Packing group III  
ICAO Packing group III

**14.5. Environmental hazards**

Environmentally Hazardous Substance/Marine Pollutant  
No.

**14.6. Special precautions for user**

EMS F-E, S-D  
Emergency Action Code 3Y  
Hazard No. (ADR) 39

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

**SECTION 15: REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

**15.2. Chemical Safety Assessment**

No chemical safety assessment has been carried out.

**SECTION 16: OTHER INFORMATION**

Revision Comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision Date 21/05/2015  
Revision 24  
Supersedes date 16/10/2013 v23  
Safety Data Sheet Status Approved.

Risk Phrases In Full

R10 Flammable  
R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.  
R20 Harmful by inhalation.  
R36/38 Irritating to eyes and skin.

Hazard Statements In Full

H372 Causes damage to organs <<Organs>> through prolonged or repeated exposure.  
H319 Causes serious eye irritation.  
H315 Causes skin irritation.  
H226 Flammable liquid and vapour.  
H332 Harmful if inhaled.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H361d Suspected of damaging the unborn child.