



Diesel Pre Emission Test Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

MSDS Version: E07.00

Date of issue: 30/08/2018

Blend Version: 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Diesel Pre Emission Test Treatment
Product code : W35392

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Diesel fuel additive
Function or use category : Fuel additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Wynn's Belgium
Industriepark-West 46
9100 Sint-Niklaas - Belgium
T +32 3 766 60 20 - F +32 3 778 16 56
msds@wynns.eu - www.wynns.com

1.4. Emergency telephone number

Emergency number : BIG: +32(0)14/58.45.45 (NL FR EN DE)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Asp. Tox. 1 H304
Aquatic Chronic 3 H412

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS08

Signal word (CLP) : Danger
Hazardous ingredients : distillates (Fischer-Tropsch), C8-26, branched and linear
Hazard statements (CLP) : H304 - May be fatal if swallowed and enters airways.
H412 - Harmful to aquatic life with long lasting effects.
EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking.
Precautionary statements (CLP) : P102 - Keep out of reach of children.
P405 - Store locked up.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor
P331 - Do NOT induce vomiting.
P273 - Avoid release to the environment.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Diesel Pre Emission Test Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

3.2. Mixtures

Name	Product identifier	% w	Classification according to Regulation (EC) No. 1272/2008 [CLP]
distillates (Fischer-Tropsch), C8-26, branched and linear	(CAS-No.) 848301-67-7 (EC-No.) 481-740-5 (REACH-no) 01-0000020119-75	>= 90	Asp. Tox. 1, H304
Hydrocarbons, C10, aromatics, <1% naphthalene	(EC-No.) 918-811-1 (REACH-no) 01-2119463583-34	1 - 2,5	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
2-ethylhexan-1-ol substance with a Community workplace exposure limit	(CAS-No.) 104-76-7 (EC-No.) 203-234-3 (REACH-no) 01-2119487289-20	0,1 - 1	Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
Naphthalene	(CAS-No.) 91-20-3 (EC-No.) 202-049-5 (EC Index-No.) 601-052-00-2 (REACH-no) 01-2119561346-37	0,1 - 1	Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Check the vital functions. Keep victim at rest in half upright position. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Keep watching the victim. Give psychological aid. Prevent cooling by covering the victim (no warming up). Keep the victim calm, avoid physical strain. If necessary seek medical advice.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Ingestion of large quantities: immediately to hospital.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. AFFF foam. ABC-powder.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid. Take precautionary measures against static discharges.

Explosion hazard : Product is not explosive.

5.3. Advice for firefighters

Firefighting instructions : Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

Protective equipment : Wear suitable gloves and eye/face protection. protective clothing.

Diesel Pre Emission Test Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Emergency procedures : Mark the danger area. Prevent flow to low areas. In confined space use self-contained breathing apparatus. Take off contaminated clothing.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage. Contain leaking substance, pump over in suitable containers.

Methods for cleaning up : Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Clean preferably with a detergent - Avoid the use of solvents.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Meet the legal requirements. Use good personal hygiene practices. Repeated exposure may cause skin dryness or cracking. Presents no particular risk when handled in accordance with good occupational hygiene practice.

Hygiene measures : Use good personal hygiene practices. IF ON SKIN: Gently wash with plenty of soap and water. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Does not require any specific or particular technical measures.

Storage conditions : Meet the legal requirements. Protect from sunlight. Store in a well-ventilated place.

Storage area : Meet the legal requirements. Ventilation along the floor.

Special rules on packaging : Meet the legal requirements. Store in a closed container. Labelling according to.

7.3. Specific end use(s)

Read label before use. Observe the label precautions. See product bulletin for detailed information.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Hydrocarbons, C10, aromatics, <1% naphthalene

Belgium Limit value (mg/m³) 200 mg/m³

2-ethylhexan-1-ol (104-76-7)

EU IOELV TWA (mg/m³) 5,4 mg/m³

EU IOELV TWA (ppm) 1 ppm

Germany TRGS 900 Occupational exposure limit value (mg/m³) 110 mg/m³

Germany TRGS 900 Occupational exposure limit value (ppm) 20 ppm

Naphthalene (91-20-3)

EU IOELV TWA (mg/m³) 50 mg/m³

EU IOELV TWA (ppm) 10 ppm

Belgium Limit value (mg/m³) 53 mg/m³

Belgium Limit value (ppm) 10 ppm

Belgium Short time value (mg/m³) 80 mg/m³

Belgium Short time value (ppm) 15 ppm

Belgium Remark (BE) D

Hungary AK-érték 50 mg/m³

distillates (Fischer-Tropsch), C8-26, branched and linear (848301-67-7)

PNEC (Sediment)

PNEC sediment (freshwater) 2,06 mg/kg dwt

PNEC (Soil)

PNEC soil 1,68 mg/kg dwt

PNEC (STP)

Diesel Pre Emission Test Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

distillates (Fischer-Tropsch), C8-26, branched and linear (848301-67-7)

PNEC sewage treatment plant 10 mg/l

Hydrocarbons, C10, aromatics, <1% naphthalene

DNEL/DMEL (Workers)

Long-term - systemic effects, dermal 12,5 mg/kg bodyweight/day

Long-term - systemic effects, inhalation 151 mg/m³

DNEL/DMEL (General population)

Long-term - systemic effects, oral 7,5 mg/kg bodyweight/day

Long-term - systemic effects, inhalation 32 mg/m³

Long-term - systemic effects, dermal 7,5 mg/kg bodyweight/day

2-ethylhexan-1-ol (104-76-7)

DNEL/DMEL (Workers)

Acute - local effects, inhalation 53,2 mg/m³

Long-term - systemic effects, dermal 23 mg/kg bodyweight/day

Long-term - systemic effects, inhalation 12,8 mg/m³

Long-term - local effects, inhalation 53,2 mg/m³

DNEL/DMEL (General population)

Acute - local effects, inhalation 26,6 mg/m³

Long-term - systemic effects, oral 1,1 mg/kg bodyweight/day

Long-term - systemic effects, inhalation 2,3 mg/m³

Long-term - systemic effects, dermal 11,4 mg/kg bodyweight/day

Long-term - local effects, inhalation 26,6 mg/m³

PNEC (Water)

PNEC aqua (freshwater) 0,017 mg/l

PNEC aqua (marine water) 0,0017 mg/l

PNEC aqua (intermittent, freshwater) 0,17 mg/l

PNEC (Sediment)

PNEC sediment (freshwater) 0,284 mg/kg dwt

PNEC sediment (marine water) 0,0284 mg/kg dwt

PNEC (Soil)

PNEC soil 0,047 mg/kg dwt

PNEC (STP)

PNEC sewage treatment plant 10 mg/l

Naphthalene (91-20-3)

DNEL/DMEL (Workers)

Long-term - systemic effects, dermal 3,57 mg/kg bodyweight/day

Long-term - systemic effects, inhalation 25 mg/m³

Long-term - local effects, inhalation 25 mg/m³

PNEC (STP)

PNEC sewage treatment plant 2,9 mg/l

8.2. Exposure controls

Appropriate engineering controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Does not require any specific or particular technical measures.

Personal protective equipment

: Gloves. Safety glasses.



Hand protection

: Neoprene. Nitrile rubber. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Time of penetration is to be checked with the glove producer.

Other information

: Breakthrough time : >30'. Thickness of the glove material >0,1 mm.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Diesel Pre Emission Test Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Colour	: brown.
Odour	: characteristic.
Odour threshold	: No data available
pH	:
Relative evaporation rate (butylacetate=1)	: No data available
refraction index	: 1,436
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 71 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density @20°C	: 779 kg/m ³
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic @40°C	: 2,69 mm ² /s
Viscosity, dynamic @40°C	: No data available
Viscosity	:
Viscosity Index	:
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 98,69 %
Additional information	: The physical and chemical data in this section are typical values for this product and are not intended as product specifications.

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from strong acids and strong oxidizers.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful: may cause lung damage if swallowed

distillates (Fischer-Tropsch), C8-26, branched and linear (848301-67-7)

LD50 oral rat > 5000 mg/kg bodyweight Sprague-Dawley

Diesel Pre Emission Test Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

distillates (Fischer-Tropsch), C8-26, branched and linear (848301-67-7)

LD50 dermal rat > 2000 mg/kg bodyweight Sprague-Dawley

Hydrocarbons, C10, aromatics, <1% naphthalene

LD50 oral rat 6318 mg/kg bodyweight CrI:CDBR
LD50 dermal rabbit > 2000 mg/kg bodyweight New Zealand White
LC50 inhalation rat (mg/l) > 4,688 mg/l/4h Sprague-Dawley
ATE CLP (oral) 6318 mg/kg bodyweight

2-ethylhexan-1-ol (104-76-7)

LD50 oral rat 3290 mg/kg
LD50 dermal rabbit > 3000 mg/kg
LC50 inhalation rat (mg/l) 1,1 mg/l/4h
ATE CLP (oral) 3290 mg/kg bodyweight
ATE CLP (dermal) 3000 mg/kg bodyweight
ATE CLP (vapours) 1,1 mg/l/4h
ATE CLP (dust,mist) 1,1 mg/l/4h

Naphthalene (91-20-3)

LD50 oral rat > 2000 mg/kg bodyweight Sprague-Dawley
LD50 dermal rat > 2500 mg/kg bodyweight Sherman
ATE CLP (oral) 500 mg/kg bodyweight
Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : This product contains hazardous components for the aquatic environment.
Ecology - water : Harmful to aquatic life with long lasting effects.

distillates (Fischer-Tropsch), C8-26, branched and linear (848301-67-7)

LC50 fish 1 > 1000 mg/l @96h Pimephales promelas
EC50 Daphnia 1 > 1000 mg/l @48h Daphnia magna
EC50 other aquatic organisms 1 > 1000 mg/l @72h Pseudokirchneriella subcapitata
NOEC (acute) > 1000 mg/l @48h Daphnia magna

Hydrocarbons, C10, aromatics, <1% naphthalene

LC50 fish 1 96h 2 - 5 mg/l Oncorhynchus mykiss
EC50 Daphnia 1 48h 10 mg/l Daphnia magna
EC50 other aquatic organisms 1 72h 1 - 3 mg/l Pseudokirchneriella subcapitata

2-ethylhexan-1-ol (104-76-7)

LC50 fish 1 96h 28,2 mg/l pimephales promelas
EC50 Daphnia 1 48h 39 mg/l daphnia magna
EC50 other aquatic organisms 1 72h 11,5 mg/l algae (desmodesmus subspicatus)

Naphthalene (91-20-3)

LC50 fish 1 96h 1,6 mg/l Oncorhynchus mykiss
EC50 Daphnia 1 48h 2,16 mg/l Daphnia magna

12.2. Persistence and degradability

distillates (Fischer-Tropsch), C8-26, branched and linear (848301-67-7)

Persistence and degradability Readily biodegradable.

Diesel Pre Emission Test Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-ethylhexan-1-ol (104-76-7)

Persistence and degradability Readily biodegradable.

12.3. Bioaccumulative potential

distillates (Fischer-Tropsch), C8-26, branched and linear (848301-67-7)

Log Pow > 6,5 @40°C

2-ethylhexan-1-ol (104-76-7)

Bioaccumulative potential No bioaccumulation.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

2-ethylhexan-1-ol (104-76-7)

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Remove to an authorized waste treatment plant. Avoid release to the environment.

European List of Waste (LoW) code : 14 06 03* - other solvents and solvent mixtures
15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

No additional information available

14.6.2. Transport by sea

No additional information available

14.6.3. Air transport

No additional information available

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list $\geq 0,1$ % / SCL

Contains no REACH Annex XIV substances

Diesel Pre Emission Test Treatment

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

VOC content : 98,69 %

15.1.2. National regulations

Water hazard class (WGK) : 1 - Slightly hazardous to water

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product